



IP
44



- Electrostatic powder coated aluminum injection body
- Fixed (unchanging) or changing color option
- Works silently, without the need for fan cooling
- Comes with up to 400 mixed fiber optic strands

*See size options in table FO package options

P W Product & Power Options

Product Name	Light Color	Input Voltage (V)	Power (W)	Weight (kg)
IK77-V2	WW-NW-CW	220-240V AC	10	0,53
IK77-V2	WW-NW-CW	12V DC	13	0,53
IK77-V2	WW-NW-CW	12V DC	18	0,53
IK77-V2	RGB	12V DC	18	0,53

C Light Color Options

● WW: Warm White	3000K	● R: Red	625nm
● NW: Natural White	4000K	● G: Green	525nm
● CW: Cold White	6500K	● B: Blue	465nm
		● A: Amber	590nm

UZ Lenght Options

0 (Only light source)	200cm
100cm	300cm
150cm	500cm

PK Package Options

100 Mixed Strand	300 Mixed Strand
150 Mixed Strand	350 Mixed Strand
200 Mixed Strand	400 Mixed Strand
250 Mixed Strand	

Fo Package Options

Fiber Optic Cable Type	100 Mixed strand (qty)	150 Mixed strand (qty)	200 Mixed strand (qty)	250 Mixed strand (qty)	300 Mixed strand (qty)	350 Mixed strand (qty)	400 Mixed strand (qty)
20	0	35	60	90	120	140	150
30	20	30	40	60	90	100	120
40	20	25	35	30	40	60	90
60	18	20	30	35	20	28	22
80	16	16	18	20	15	10	10
100	14	12	10	10	9	6	4
120	12	12	7	5	6	6	4

Control System Options

Color Type	PWM	INV PWM	DMX	DALI	0-10V DC	TRIAC
WW-NW-CW	●				●	
R,G,B,A	●				●	
RGB	●					
RGBA/W						
RGB DMX						
WHITE DMX						



Order Code

P . W . C . UZ . PK

