



- Min. 20 micron anodized aluminum extruded profile
- High efficient homogeneous light by plexiglas diffused cover
- Suitable for pendant mounting
- Various sizes are applicable
- Different colors are applicable for the housing
- 1,5 m steel wire hangers are included
- The number of the hangers in the package may vary regarding the product size

P W Product & Power Options

Product Name	Light Color	Input Voltage (V)	Power (W)	Luminous Flux (lm)	Weight (kg)
BLZ-PUZZLE	WW-NW-CW	24V DC	250	20.000	14,3
BLZ-PUZZLE	WW-NW-CW	24V DC	500	40.000	14,3

*Power and Lumen values provided are based off of a cold white (CW) LED.

C Light Color Options

● WW: Warm White	3000K
● NW: Natural White	4000K
● CW: Cold White	6500K

G Housing Color/Coating Options



01: Anodized RAL9005 RAL9016 29: Walnut 30: Dark Walnut 31: Oak 32: Light Walnut

Control System Options

Color Type	PWM	INV PWM	DMX	DALI	0-10V DC	TRIAC
WW-NW-CW	●			●	●	
R,G,B,A						
RGB						
RGBA/W						
RGB DMX						
WHITE DMX						



Lotus Mall, Russia



Order Code

P . W . C . G



DecoPendant

